Safety Data Sheet (SDS)



Moly Maxi 6000 ISO 220

SDS Number: 11092

Revision Date: 1/19/2015

Page 1 of 4

Section 1: Product and Company Identification

Manufacturer

Bade Incorporated 48 Sulfer Spring Road Irwin, PA 15642

Phone: 1-888-783-0363

Product Name:	Moly Maxi 6000 ISO 220
Revision Date:	1/19/2015
SDS Number:	11092
Common Name:	Hydrotreated heavy paraffinic oil
CAS Number:	Blend
Product Code:	11092
Synonyms:	Zinc Free Antiwear Hydraulic Fluid

For emergencies contact Chemtrec at 1-800-424-9300.

2. Hazard Identification

GHS Signal Word: NONE

GHS Classifications: None, None, None

GHS Phrases: H000 - None

3. Composition/Information on Ingredients

Ingredients:

Chemical Name	Percentage	CASE #
Petroleum, solvent dewaxed heavy paraffinic oil	> 98	64742-65-0
Additives	< 3	Proprietary

Safety Data Sheet



Moly Maxi 6000 ISO 220

SDS Number: 11092

Revision Date: 1/19/2015 Page 2 of 4

4. First Aid Measures Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. Skin Contact: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed. Eye Contact: Flush with water for several minutes. If effects occur, consult a physician. Ingestion: Rinse mouth with water. If symptoms develop, obtain medical attention.

5. Fire Fighting Measures

Flash Point:	248.9 C (480.0 F)
Flash Point	COC
Method:	

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

6. Accidental Release Measures

Contain spilled material. Collect insuitable and properly labeled containers. Pick up excess with inertabsorbent material. Keep away from drains and ground water.

7. Handling and Storage Handling Precautions: Avoid contact with eyes, skin, or clothing. Keep away from sources of ignition. Handle with care and avoid spillage on the floor (slippage).

Storage Requirements: Keep away from sources of ignition.

Safety Data Sheet (SDS)



,			
	Moly	Maxi 6000 ISO 220	
SDS Number: 11092	2		Revision Date: 1/19/2015
			Page 3 of 4
0 E 0			<u> </u>
8. Exposure Contro	ols/Personal Protection		
Engineering Controls	All ventilation should be de	esigned in accordance with OSHA	standard (20 CER 1910 94)
			Standard (2001 11 1010.04).
Personal Protection I	Equip: Use of safety glasses and glo	vesare recommended.	
9. Physical and Cl	nemical Properties		
	lennear roperties		
Appearance:	Amber		
Physical State:	Liquid	Solubility:	Nilinwater
Viscosity:	220 cSt at 40 degrees C	Percent Volatile:	Nil
Boiling Point:	> 425 F		
10. Stability and Re	activity		
Stability:	Product is stable under normal conditior	ns.	
Conditions to Avoid:	High temperatures and open flame.		
11. Toxicological In	oformation		
Repeated skin contact w	vith this product may cause dermatitis or	an oil acne.	
No test data available or			
No component is listed a	as a carcinogen, mutagen, or teratogen.		
LD50 / LC50 - No data a			
12. Ecological Infor	mation		
	maton		
Avoid exposing to the er	nvironment, no specific aquatic data avai	ilable	

13. Disposal Considerations

Dispose of in accordance with local regulations.

Do not flush to surface water or drains.

14. Transport Information

Not regulated by DOT.

Safety Data Sheet (SDS)



Moly Maxi 6000 ISO 220

SDS Number: 11092

Revision Date: 1/19/2015 Page 4 of 4

15. Regulatory Information

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act (TSCA).

16. Other Information

The information contained in this Safety Data Sheet relates only to the specific material designated. Bade Incorporated assumes no legal responsibility for use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Bade Incorporated.